

CHILD RESTRAINT SYSTEM INFORMATION

MODEL **LB509 (AURA)**

GROUP **I / II / III**

BRAND **CROLLA**



0090289




UNR TESTING INFORMATION

| | |
|----------------------|--------------------------------|
| Regulation | ECE R44/04 |
| Approval Number | E13*44R00*44R04*5104*02 |
| CTA Reference Number | JPJ.BKA.600-3/3/33 Jld 70 (28) |
| CTA Approval Date | 5 AUGUST 2020 |

INSTALLATION TYPE

| Installation Type/ Direction | Seatbelt | ISOFIX | Top Tether | Support Leg |
|------------------------------|----------|--------|------------|-------------|
| Rear Facing | N/A | N/A | N/A | N/A |
| Forward Facing | ✓ | N/A | N/A | N/A |

PHOTOS

| | Front view | Left view | Rear view | Right view |
|----------------|---|---|--|---|
| Rear Facing | N/A | N/A | N/A | N/A |
| Forward Facing |  |  |  |  |

CHILD RESTRAINT SYSTEM INFORMATION

COLOUR VARIANT



INSTALLATION

Group

Installation Method

0/0+
Up to 83cm
0-13kg

N/A


1
71cm and above
9-18kg



Step 1. Place the child safety seat on the vehicle's seat ensuring it is firmly pressed against the car seat backrest.



Step 2: Thread the car seat belt passes through the cushion of the backrest of the car seat following the seat belt route. Put the car safety belt tongue into the car buckle.



Step 3 Check the webbing of the seat belt has not become twisted or tangled and that the lap belt goes between the backrest and seat body, and the diagonal belt goes over the red belt guide fixed on the backrest and make sure it is under the headrest. Then out through the other seat belt route slot and fasten it into the seat belt buckle until you heard "click".



Step 4. Place your knee on the base of the safety seat and grip the top piece of seat belt webbing. Pull the webbing upwards to tighten the seat belt. then you can place your child into the safety seat. Check the height of the shoulder straps on the correct position.

CHILD RESTRAINT SYSTEM INFORMATION

2

100cm and above
15-25kg



Step1.Place the child safety seat on the vehicle's seat ensuring it is firmly pressed against the car seat backrest.



Step2.Place the child in the child safety seat .



Step 3: Pull the vehicle safety belt and pass through the belt path, and then buckle it up. Position shoulder belt through the shoulder belt guide as shown in photo.



Step 4: DO NOT position vehicle belt over top of the armrests. It must pass underneath the armrests. Belt must not be twisted.



Step1.Place the child safety seat on the vehicle's seat ensuring it is firmly pressed against the car seat backrest.



Step2.Place the child in the child safety seat .



Step 3: Pull the vehicle safety belt and pass through the belt path, and then buckle it up. Position shoulder belt through the shoulder belt guide as shown in photo.



Step 4: DO NOT position vehicle belt over top of the armrests. It must pass underneath the armrests. Belt must not be twisted.

3

Up to 135cm
22-36kg